Apparatus Licence

Issued by Delegate of the Australian Communications and Media Authority



Licensee details		
Customer ID	1611641	
Licensee	ARC INFRASTRUCTURE PTY LTD	
Trading name	ARC INFRASTRUCTURE PTY LTD	
Licensee address	Level 3, 1 George Wiencke Attn : Wayne Belstead, PERTH AIRPORT, WA 6845	

Licence details		
Licence service	Fixed	
Licence subservice	Point to Point	
Licence number	289953/1	
Date of issue	09/05/2024	
Date of effect	09/05/2024	
Date of expiry	12/05/2025	

Licence conditions

Your licence is subject to conditions set out in the *Radiocommunications Act 1992*. Your licence may also be subject to such other licence conditions as determined by the ACMA (in licence condition determinations) from time to time, and is also subject to special conditions as detailed on this licence.

The conditions that are imposed on a licence vary according to the type of licence issued, the service being operated and the section of the *Radiocommunications Act 1992* under which the licence has been issued. For further information about the conditions that apply to your licence, please contact the ACMA (see contact details below).

Rights of appeal

A decision by the ACMA to impose further conditions or revoke or vary the conditions of your licence may be reviewable. If you are affected by, and dissatisfied with, such a decision you may apply to the ACMA to have the ACMA reconsider the decision under section 288 of the *Radiocommunications Act 1992*.

An application for reconsideration must state the reasons for the request, and should be sent to the Customer Service Centre, Australian Communications and Media Authority, PO Box 78, Belconnen, ACT, 2616. Applications for review of decisions can be made using the R051 - Application for review of Decision form, available on the ACMA website.

Important

An application for the ACMA to reconsider a decision to impose or vary licence conditions must be made to the ACMA within 28 days of the day on which you are informed of the decision. An application for reconsideration made after that time may not be accepted.

ACMA contact details

Customer Service Centre PO Box 78 BELCONNEN ACT 2616

Telephone: 1300 850 115 Email: info@acma.gov.au

ACMA website: www.acma.gov.au

Certain information contained in this licence record will be disclosed in the Register of Radiocommunications Licences (RRL), established and maintained pursuant to Part 3.5 of the *Radiocommunications Act 1992*.

Fixed - Point to Point Page 1 of 3

Advisory Notes applying to licence no.: 289953/1

Conditions applicable to the operation of Point to Point station(s) authorised under this licence can be found in the Radiocommunications Licence Conditions (Apparatus Licence) Determination and the Radiocommunications Licence Conditions (Fixed Licence) Determination, the 'fixed licence lcd'. Copies of these determinations are available from the ACMA and from the ACMA home page (www.acma.gov.au).

Fixed - Point to Point Page 2 of 3

Technical characteristics

Below is a summary of the technical characteristics of the licensed service. Further technical details not displayed here may be found on the ACMA website.

Link 1

Site details	Site 1	Site 2		
Site ID	28477	600009		
Site address	Telstra Mast City of Albany Site, Mt Melville off Melville Drv, MOUNT MELVILLE WA 6330	Westrail New, MT Barrow, MT BARKER WA 6324		
Co-ordinates (GDA94)	Lat: -35.017898 Long: 117.87082	Lat: -34.627242 Long: 117.708765		
Equipment details:				
Assigned TX frequency	414.425000 MHz	404.975000 MHz		
Assigned RX frequency	404.975000 MHz	414.425000 MHz		
Bandwidth	25.0000 kHz	25.0000 kHz		
Freq. assign. ID	0000579184	0000579186		
Transmitter power	1.00 W	1.00 W		
EIRP				
Emission designator	16K0F3E	16K0F3E		
Antenna details				
Antenna ID	70073	70073		
Antenna polarisation	H - Horizontal linear	H - Horizontal linear		
Antenna azimuth	341.07	161.16		
Antenna height (m)	0.00	0.00		
Antenna type	Yagi (Horizontal Polarisation)-Y	Yagi (Horizontal Polarisation)-Y		

Special Conditions applying to Station 1

When the transmitter is coupled to an antenna the level of all discrete spurious components caused by the transmitter & measured at the connection to the antenna must not exceed -30 DBM. Broadband noise floor of the transmitter measured at the same point must not exceed -47 DBM in a 16 kHz bandwidth for frequency offsets greater than 300 kHz from the transmit frequency.

Special Conditions applying to Station 2

The level of power in the adjacent channel must not exceed -22dBm.

Fixed - Point to Point Page 3 of 3