Apparatus Licence

Issued by Delegate of the Australian Communications and Media Authority

Australian Government | acma

Licensee details

Customer ID	159310
Licensee	THE WIRELESS INSTITUTE OF AUSTRALIA VICTORIAN DIVISION
Trading name	The Wireless Institute of Australia Victorian Division
Licensee address	9 Carrington Street, SYDENHAM, VIC 3037

Licence details

Licence service	Amateur
Licence subservice	Amateur Repeater
Licence number	1184438/1
Callsign	VK3RDG
Date of issue	16/02/2024
Date of effect	16/02/2024
Date of expiry	25/03/2025

Licence conditions

Your licence is subject to conditions set out in the *Radiocommunications Act 1992*. Your licence may also be subject to such other licence conditions as determined by the ACMA (in licence condition determinations) from time to time, and is also subject to special conditions as detailed on this licence.

The conditions that are imposed on a licence vary according to the type of licence issued, the service being operated and the section of the *Radiocommunications Act 1992* under which the licence has been issued. For further information about the conditions that apply to your licence, please contact the ACMA (see contact details below).

Rights of appeal

A decision by the ACMA to impose further conditions or revoke or vary the conditions of your licence may be reviewable. If you are affected by, and dissatisfied with, such a decision you may apply to the ACMA to have the ACMA reconsider the decision under section 288 of the *Radiocommunications Act 1992*.

An application for reconsideration must state the reasons for the request, and should be sent to the Customer Service Centre, Australian Communications and Media Authority, PO Box 78, Belconnen, ACT, 2616. Applications for review of decisions can be made using the R051 - Application for review of Decision form, available on the ACMA website.

Important

An application for the ACMA to reconsider a decision to impose or vary licence conditions must be made to the ACMA within 28 days of the day on which you are informed of the decision. An application for reconsideration made after that time may not be accepted.

ACMA contact details

Customer Service Centre
PO Box 78
BELCONNEN ACT 2616

Telephone: 1300 850 115
Email: info@acma.gov.au

ACMA website: www.acma.gov.au

Certain information contained in this licence record will be disclosed in the Register of Radiocommunications Licences (RRL), established and maintained pursuant to Part 3.5 of the *Radiocommunications Act 1992.*

Advisory Notes applying to licence no.: 1184438/1

Conditions applicable to the operation of Amateur Repeater station(s) authorised under this licence can be found in the Radiocommunications Licence Conditions (Apparatus Licence) Determination and the Radiocommunications Licence Conditions (Amateur Licence) Determination. Copies of these determinations are available from the ACMA and from the ACMA home page (www.acma.gov.au).

Technical characteristics

Below is a summary of the technical characteristics of the licensed service. Further technical details not displayed here may be found on the ACMA website.

Main Station Site **Station 1:**

Site details	
Site ID	12087
Site address	Police Site, MT DELEGATE VIC 3888
Co-ordinates (GDA94)	Latitude: -37.112673 Longitude: 148.897344

Transmitter details	
Assigned frequency	144.900000 MHz
Bandwidth	25.0000 kHz
Freq. assign. ID	0000516751
Transmitter power	50.00 W
EIRP	
Emission designator	16K0F2D
Antenna details	
Antenna ID	60066
Antenna polarisation	V - Vertical linear
Antenna azimuth	
Antenna height (m)	0
Antenna type	Colinear Vertical-U

Receiver details	
Assigned frequency	144.900000 MHz
Bandwidth	25.0000 kHz
Freq. assign. ID	0000516752
Transmitter power	N/A
EIRP	N/A
Emission designator	16K0F2D
Antenna details	
Antenna ID	60066
Antenna polarisation	V - Vertical linear
Antenna azimuth	
Antenna height (m)	0
Antenna type	Colinear Vertical-U

Special Conditions applying to Station 1

When the transmitter is coupled to an antenna the level of all discrete spurious components caused by the transmitter & measured at the connection to the antenna must not exceed -30 DBM. Broadband noise floor of the transmitter measured at the same point must not exceed -47 DBM in a 16 kHz bandwidth for frequency offsets greater than 300 kHz from the transmit frequency.

Technical characteristics

Below is a summary of the technical characteristics of the licensed service. Further technical details not displayed here may be found on the ACMA website.

Main Station Site **Station 2:**

Site details	
Site ID	12087
Site address	Police Site, MT DELEGATE VIC 3888
Co-ordinates (GDA94)	Latitude: -37.112673 Longitude: 148.897344

Transmitter details	
Assigned frequency	145.175000 MHz
Bandwidth	25.0000 kHz
Freq. assign. ID	0000516753
Transmitter power	50.00 W
EIRP	
Emission designator	16K0F2D
Antenna details	
Antenna ID	60066
Antenna polarisation	V - Vertical linear
Antenna azimuth	
Antenna height (m)	0
Antenna type	Colinear Vertical-U

Receiver details	
Assigned frequency	145.175000 MHz
Bandwidth	25.0000 kHz
Freq. assign. ID	0000516754
Transmitter power	N/A
EIRP	N/A
Emission designator	16K0F2D
Antenna details	
Antenna ID	60066
Antenna polarisation	V - Vertical linear
Antenna azimuth	
Antenna height (m)	0
Antenna type	Colinear Vertical-U

Special Conditions applying to Station 2

When the transmitter is coupled to an antenna the level of all discrete spurious components caused by the transmitter & measured at the connection to the antenna must not exceed -30 DBM. Broadband noise floor of the transmitter measured at the same point must not exceed -47 DBM in a 16 kHz bandwidth for frequency offsets greater than 300 kHz from the transmit frequency.

Technical characteristics

Below is a summary of the technical characteristics of the licensed service. Further technical details not displayed here may be found on the ACMA website.

Main Station Site **Station 3:**

Site details	
Site ID	12087
Site address	Police Site, MT DELEGATE VIC 3888
Co-ordinates (GDA94)	Latitude: -37.112673 Longitude: 148.897344

Transmitter details	
Assigned frequency	439.100000 MHz
Bandwidth	25.0000 kHz
Freq. assign. ID	0000516755
Transmitter power	50.00 W
EIRP	
Emission designator	16K0F2D
Antenna details	
Antenna ID	60005
Antenna polarisation	V - Vertical linear
Antenna azimuth	
Antenna height (m)	0
Antenna type	Colinear Vertical-U

Receiver details	
Assigned frequency	439.100000 MHz
Bandwidth	25.0000 kHz
Freq. assign. ID	0000516756
Transmitter power	N/A
EIRP	N/A
Emission designator	16K0F2D
Antenna details	
Antenna ID	60005
Antenna polarisation	V - Vertical linear
Antenna azimuth	
Antenna height (m)	0
Antenna type	Colinear Vertical-U

Special Conditions applying to Station 3

When the transmitter is coupled to an antenna the level of all discrete spurious components caused by the transmitter & measured at the connection to the antenna must not exceed -30 DBM. Broadband noise floor of the transmitter measured at the same point must not exceed -47 DBM in a 16 kHz bandwidth for frequency offsets greater than 300 kHz from the transmit frequency.

Technical characteristics

Below is a summary of the technical characteristics of the licensed service. Further technical details not displayed here may be found on the ACMA website.

Main Station Site **Station 4:**

Site details	
Site ID	12087
Site address	Police Site, MT DELEGATE VIC 3888
Co-ordinates (GDA94)	Latitude: -37.112673 Longitude: 148.897344

Transmitter details	
Assigned frequency	147.125000 MHz
Bandwidth	25.0000 kHz
Freq. assign. ID	0000516757
Transmitter power	50.00 W
EIRP	
Emission designator	16K0F3E
Antenna details	
Antenna ID	60066
Antenna polarisation	V - Vertical linear
Antenna azimuth	
Antenna height (m)	0
Antenna type	Colinear Vertical-U

Receiver details	
Assigned frequency	147.725000 MHz
Bandwidth	25.0000 kHz
Freq. assign. ID	0000516758
Transmitter power	N/A
EIRP	N/A
Emission designator	16K0F3E
Antenna details	
Antenna ID	60066
Antenna polarisation	V - Vertical linear
Antenna azimuth	
Antenna height (m)	0
Antenna type	Colinear Vertical-U

Special Conditions applying to Station 4

When the transmitter is coupled to an antenna the level of all discrete spurious components caused by the transmitter & measured at the connection to the antenna must not exceed -30 DBM. Broadband noise floor of the transmitter measured at the same point must not exceed -47 DBM in a 16 kHz bandwidth for frequency offsets greater than 300 kHz from the transmit frequency.