# Apparatus Licence

Issued by Delegate of the Australian Communications and Media Authority



Licensee details	
Customer ID	20026647
Licensee	NSW Electricity Networks Operations Pty Limited
Trading name	NSW Electricity Networks Operations Pty Limited
Licensee address	180 Thomas Street, HAYMARKET, NSW 2000

Licence details	
Licence service	Fixed
Licence subservice	Point to Point
Licence number	1192329/2
Callsign	VL2AM
Date of issue	05/06/2023
Date of effect	05/06/2023
Date of expiry	10/05/2024

### Licence conditions

Your licence is subject to conditions set out in the *Radiocommunications Act 1992*. Your licence may also be subject to such other licence conditions as determined by the ACMA (in licence condition determinations) from time to time, and is also subject to special conditions as detailed on this licence.

The conditions that are imposed on a licence vary according to the type of licence issued, the service being operated and the section of the *Radiocommunications Act 1992* under which the licence has been issued. For further information about the conditions that apply to your licence, please contact the ACMA (see contact details below).

#### Rights of appeal

A decision by the ACMA to impose further conditions or revoke or vary the conditions of your licence may be reviewable. If you are affected by, and dissatisfied with, such a decision you may apply to the ACMA to have the ACMA reconsider the decision under section 288 of the *Radiocommunications Act 1992*.

An application for reconsideration must state the reasons for the request, and should be sent to the Customer Service Centre, Australian Communications and Media Authority, PO Box 78, Belconnen, ACT, 2616. Applications for review of decisions can be made using the R051 - Application for review of Decision form, available on the ACMA website.

#### **Important**

An application for the ACMA to reconsider a decision to impose or vary licence conditions must be made to the ACMA within 28 days of the day on which you are informed of the decision. An application for reconsideration made after that time may not be accepted.

### **ACMA** contact details

Customer Service Centre PO Box 78 BELCONNEN ACT 2616

Telephone: 1300 850 115 Email: info@acma.gov.au

ACMA website: www.acma.gov.au

Certain information contained in this licence record will be disclosed in the Register of Radiocommunications Licences (RRL), established and maintained pursuant to Part 3.5 of the *Radiocommunications Act 1992*.

Fixed - Point to Point Page 1 of 3

# Advisory Notes applying to licence no.: 1192329/2

Conditions applicable to the operation of Point to Point station(s) authorised under this licence can be found in the Radiocommunications Licence Conditions (Apparatus Licence) Determination and the Radiocommunications Licence Conditions (Fixed Licence) Determination, the 'fixed licence lcd'. Copies of these determinations are available from the ACMA and from the ACMA home page (www.acma.gov.au).

Fixed - Point to Point Page 2 of 3

### Technical characteristics

Below is a summary of the technical characteristics of the licensed service. Further technical details not displayed here may be found on the ACMA website.

### Link 1

Site details	Site 1	Site 2		
Site ID	9901	9755		
Site address	Clarkes Hill, Tooma Road via, TUMBARUMBA NSW 2653	Upper Tumut Switching Station, UPPER TUMUT NSW 2720		
Co-ordinates (GDA94)	Lat: -35.881316 Long: 148.121849	Lat: -35.909842 Long: 148.386001		
Equipment details:				
Assigned TX frequency	44.730000 MHz	42.730000 MHz		
Assigned RX frequency	42.730000 MHz	44.730000 MHz		
Bandwidth	25.0000 kHz	25.0000 kHz		
Freq. assign. ID	0000621520	0000621522		
Transmitter power	25.00 W	25.00 W		
EIRP		0 mW		
Emission designator	16K0F3E	16K0F3E		
Antenna details				
Antenna ID	13326	13326		
Antenna polarisation	V - Vertical linear	V - Vertical linear		
Antenna azimuth	97.64	277.48		
Antenna height (m)	12	22		
Antenna type	Yagi (Horizontal Polarisation)-Y	Yagi (Horizontal Polarisation)-Y		

## Special Conditions applying to Station 0 Site 1

The level of power in the adjacent channel must not exceed -22dBm.

When the transmitter is coupled to an antenna the level of all discrete spurious components caused by the transmitter & measured at the connection to the antenna must not exceed -30 DBM. Broadband noise floor of the transmitter measured at the same point must not exceed -47 DBM in a 16 kHz bandwidth for frequency offsets greater than 300 kHz from the transmit frequency.

### Special Conditions applying to Station 0 Site 2

The level of power in the adjacent channel must not exceed -22dBm.

When the transmitter is coupled to an antenna the level of all discrete spurious components caused by the transmitter & measured at the connection to the antenna must not exceed -30 DBM. Broadband noise floor of the transmitter measured at the same point must not exceed -47 DBM in a 16 kHz bandwidth for frequency offsets greater than 300 kHz from the transmit frequency.

Fixed - Point to Point Page 3 of 3