# Apparatus Licence

Issued by Delegate of the Australian Communications and Media Authority



Licensee details	
Customer ID	5832
Licensee	NSW Rural Fire Service
Trading name	
Licensee address	Locked Mail Bag 17, GRANVILLE, NSW 2142

Licence details		
Licence service	Fixed	
Licence subservice	Point to Point	
Licence number	1218521/1	
Callsign	VL2OR	
Date of issue	21/05/2023	
Date of effect	21/05/2023	
Date of expiry	29/06/2024	

### Licence conditions

Your licence is subject to conditions set out in the *Radiocommunications Act 1992*. Your licence may also be subject to such other licence conditions as determined by the ACMA (in licence condition determinations) from time to time, and is also subject to special conditions as detailed on this licence.

The conditions that are imposed on a licence vary according to the type of licence issued, the service being operated and the section of the *Radiocommunications Act 1992* under which the licence has been issued. For further information about the conditions that apply to your licence, please contact the ACMA (see contact details below).

#### Rights of appeal

A decision by the ACMA to impose further conditions or revoke or vary the conditions of your licence may be reviewable. If you are affected by, and dissatisfied with, such a decision you may apply to the ACMA to have the ACMA reconsider the decision under section 288 of the *Radiocommunications Act 1992*.

An application for reconsideration must state the reasons for the request, and should be sent to the Customer Service Centre, Australian Communications and Media Authority, PO Box 78, Belconnen, ACT, 2616. Applications for review of decisions can be made using the R051 - Application for review of Decision form, available on the ACMA website.

#### **Important**

An application for the ACMA to reconsider a decision to impose or vary licence conditions must be made to the ACMA within 28 days of the day on which you are informed of the decision. An application for reconsideration made after that time may not be accepted.

#### **ACMA** contact details

Customer Service Centre PO Box 78 BELCONNEN ACT 2616

Telephone: 1300 850 115 Email: info@acma.gov.au

ACMA website: www.acma.gov.au

Certain information contained in this licence record will be disclosed in the Register of Radiocommunications Licences (RRL), established and maintained pursuant to Part 3.5 of the *Radiocommunications Act 1992*.

Fixed - Point to Point Page 1 of 3

## Advisory Notes applying to licence no.: 1218521/1

Conditions applicable to the operation of Point to Point station(s) authorised under this licence can be found in the Radiocommunications Licence Conditions (Apparatus Licence) Determination and the Radiocommunications Licence Conditions (Fixed Licence) Determination, the 'fixed licence lcd'. Copies of these determinations are available from the ACMA and from the ACMA home page (www.acma.gov.au).

Fixed - Point to Point Page 2 of 3

### Technical characteristics

Below is a summary of the technical characteristics of the licensed service. Further technical details not displayed here may be found on the ACMA website.

### Link 1

Site details	Site 1	Site 2		
Site ID	34919	201622		
Site address	NSWRFS 40m Lattice Tower, Mt Mary, off 1720 Grabben Gullen Rd, GURRUNDAH NSW 2581	Goulburn Mulwaree Council 30m and 40m Lattice Towers, off Bannaby Road, BANNABY HILL NSW 2580		
Co-ordinates (GDA94)	Lat: -34.635539 Long: 149.350256	Lat: -34.407278 Long: 149.891601		
Equipment details:				
Assigned TX frequency	413.800000 MHz	404.350000 MHz		
Assigned RX frequency	404.350000 MHz	413.800000 MHz		
Bandwidth	25.0000 kHz	25.0000 kHz		
Freq. assign. ID	0000631097	0000631099		
Transmitter power	1.00 W	1.00 W		
EIRP		0 mW		
Emission designator	16K0F2D	16K0F2D		
Antenna details				
Antenna ID	60288	60288		
Antenna polarisation	H - Horizontal linear	H - Horizontal linear		
Antenna azimuth	63.17	242.86		
Antenna height (m)	0	0		
Antenna type	Yagi (Horizontal Polarisation)-Y	Yagi (Horizontal Polarisation)-Y		

### Special Conditions applying to Station 0 Site 1

The level of power in the adjacent channel must not exceed -22dBm.

The level of all discreet spurious components, measured at the output of the transmitter, must not exceed -30dBm.

### Special Conditions applying to Station 0 Site 2

The level of power in the adjacent channel must not exceed -22dBm.

The level of all discreet spurious components, measured at the output of the transmitter, must not exceed -30dBm.

Fixed - Point to Point Page 3 of 3