Apparatus Licence

Issued by Delegate of the Australian Communications and Media Authority



Licensee details	
Customer ID	20011154
Licensee	DEPARTMENT OF JUSTICE AND COMMUNITY SAFETY
Trading name	RMR Regional Mobile Radio
Licensee address	C/- Level 2 Bld M5 30 Henderson Rd, CLAYTON, VIC 3168

Licence details	
Licence service	Land Mobile
Licence subservice	Land Mobile System - > 30MHz
Licence number	12242097/1
Callsign	AXC321
Date of issue	31/10/2023
Date of effect	31/10/2023
Date of expiry	24/06/2024

Licence conditions

Your licence is subject to conditions set out in the *Radiocommunications Act 1992*. Your licence may also be subject to such other licence conditions as determined by the ACMA (in licence condition determinations) from time to time, and is also subject to special conditions as detailed on this licence.

The conditions that are imposed on a licence vary according to the type of licence issued, the service being operated and the section of the *Radiocommunications Act 1992* under which the licence has been issued. For further information about the conditions that apply to your licence, please contact the ACMA (see contact details below).

Rights of appeal

A decision by the ACMA to impose further conditions or revoke or vary the conditions of your licence may be reviewable. If you are affected by, and dissatisfied with, such a decision you may apply to the ACMA to have the ACMA reconsider the decision under section 288 of the *Radiocommunications Act 1992*.

An application for reconsideration must state the reasons for the request, and should be sent to the Customer Service Centre, Australian Communications and Media Authority, PO Box 78, Belconnen, ACT, 2616. Applications for review of decisions can be made using the R051 - Application for review of Decision form, available on the ACMA website.

Important

An application for the ACMA to reconsider a decision to impose or vary licence conditions must be made to the ACMA within 28 days of the day on which you are informed of the decision. An application for reconsideration made after that time may not be accepted.

ACMA contact details

Customer Service Centre PO Box 78 BELCONNEN ACT 2616

Telephone: 1300 850 115

Email: info@acma.gov.au

ACMA website: www.acma.gov.au

Certain information contained in this licence record will be disclosed in the Register of Radiocommunications Licences (RRL), established and maintained pursuant to Part 3.5 of the *Radiocommunications Act 1992*.

Advisory Notes applying to licence no.: 12242097/1

Conditions applicable to the operation of Land Mobile System station(s) authorised under this licence can be found in the Radiocommunications Licence Conditions (Apparatus Licence) Determination and the Radiocommunications Licence Conditions (Land Mobile Licence) Determination. Copies of these determinations are available from the ACMA and from the ACMA home page (www.acma.gov.au).

Technical characteristics

Below is a summary of the technical characteristics of the licensed service. Further technical details not displayed here may be found on the ACMA website.

Main Station Site

Station 1:

Site details	
Site ID	50540
Site address	CMTS Site, Lot 1 Woodland Drive, MT GISBORNE VIC 3437
Co-ordinates (GDA94)	Latitude: -37.518191 Longitude: 144.583762

Transmitter details		
	165.350000 MHz	
Assigned frequency		
Bandwidth	12.5000 kHz	
Freq. assign. ID	0004292710	
Transmitter power	50.00 W	
EIRP	83.00 W	
Emission designator	10K1F9W	
Antenna details		
Antenna ID	60308	
Antenna polarisation	V - Vertical linear	
Antenna azimuth		
Antenna height (m)	36	
Antenna type	Dipole-D	
Receiver details		
Assigned frequency	169.950000 MHz	
Bandwidth	12.5000 kHz	
Freq. assign. ID	0004292711	
Transmitter power	N/A	
EIRP	N/A	
Emission designator	10K1F9W	
Antenna details		
Antenna ID	60308	
Antenna polarisation	V - Vertical linear	
Antenna azimuth		
Antenna height (m)	36	
Antenna type	Dipole-D	

Special Conditions applying to Station 1

The level of power in the adjacent channel must not exceed -16dBm.

The level of all discreet spurious components, measured at the output of the transmitter, must not exceed -30dBm.