

Apparatus Licence

Issued by Delegate of the Australian Communications and Media Authority



Licensee details

Customer ID	20013687
Licensee	SYDNEY TRAINS
Licensee address	Attn: Mr Christopher Go Level 2, Clyde Hub, 146-148 Manchester Road, Clyde, NSW 2142

Licence details

Licence service	Land Mobile
Licence subservice	Land Mobile System - > 30MHz
Licence number	1234083/1
Callsign	VL2RW
Date of issue	04/12/2023
Date of effect	04/12/2023
Date of expiry	01/12/2024

Licence conditions

Your licence is subject to conditions set out in the *Radiocommunications Act 1992*. Your licence may also be subject to such other licence conditions as determined by the ACMA (in licence condition determinations) from time to time, and is also subject to special conditions as detailed on this licence.

The conditions that are imposed on a licence vary according to the type of licence issued, the service being operated and the section of the *Radiocommunications Act 1992* under which the licence has been issued. For further information about the conditions that apply to your licence, please contact the ACMA (see contact details below).

Rights of appeal

A decision by the ACMA to impose further conditions or revoke or vary the conditions of your licence may be reviewable. If you are affected by, and dissatisfied with, such a decision you may apply to the ACMA to have the ACMA reconsider the decision under section 288 of the *Radiocommunications Act 1992*.

An application for reconsideration must state the reasons for the request, and should be sent to the Customer Service Centre, Australian Communications and Media Authority, PO Box 78, Belconnen, ACT, 2616. Applications for review of decisions can be made using the R051 - Application for review of Decision form, available on the ACMA website.

Important

An application for the ACMA to reconsider a decision to impose or vary licence conditions must be made to the ACMA within 28 days of the day on which you are informed of the decision. An application for reconsideration made after that time may not be accepted.

ACMA contact details

Customer Service Centre
PO Box 78
BELCONNEN ACT 2616

Telephone: 1300 850 115
Email: info@acma.gov.au

ACMA website: www.acma.gov.au

Advisory Notes applying to licence no.: 1234083/1

Conditions applicable to the operation of Land Mobile System station(s) authorised under this licence can be found in the Radiocommunications Licence Conditions (Apparatus Licence) Determination and the Radiocommunications Licence Conditions (Land Mobile Licence) Determination. Copies of these determinations are available from the ACMA and from the ACMA home page (www.acma.gov.au).

Technical characteristics

Below is a summary of the technical characteristics of the licensed service. Further technical details not displayed here may be found on the ACMA website.

Main Station Site

Station 1:

Site details

Site ID	200575
Site address	Clyde marshalling yards, CLYDE NSW 2144
Co-ordinates (GDA94)	Latitude: -33.84153567 Longitude: 151.02514286

Transmitter details

Assigned frequency	418.287500 MHz
Bandwidth	12.5000 kHz
Freq. assign. ID	0000692635
Transmitter power	50.00 W
EIRP	83.00 W
Emission designator	10K1F3E

Antenna details

Antenna ID	74
Antenna polarisation	V - Vertical linear
Antenna azimuth	
Antenna height (m)	0
Antenna type	Colinear Vertical-U

Receiver details

Assigned frequency	408.837500 MHz
Bandwidth	12.5000 kHz
Freq. assign. ID	0000692638
Transmitter power	N/A
EIRP	N/A
Emission designator	10K1F3E

Antenna details

Antenna ID	74
Antenna polarisation	V - Vertical linear
Antenna azimuth	
Antenna height (m)	0
Antenna type	Colinear Vertical-U

Special Conditions applying to Station 1

The level of power in the adjacent channel must not exceed -16dBm.

The level of all discreet spurious components, measured at the output of the transmitter, must not exceed -30dBm.

Technical characteristics

Below is a summary of the technical characteristics of the licensed service. Further technical details not displayed here may be found on the ACMA website.

Supplementary Station Site

Station 2:

Site details

Site ID	5418
Site address	Within Car Sheds, MORTDALE NSW 2223
Co-ordinates (GDA94)	Latitude: -33.97801438 Longitude: 151.07968006

Transmitter details

Assigned frequency	418.287500 MHz
Bandwidth	12.5000 kHz
Freq. assign. ID	0000692631
Transmitter power	25.00 W
EIRP	41.00 W
Emission designator	10K1F3E

Antenna details

Antenna ID	70085
Antenna polarisation	V - Vertical linear
Antenna azimuth	
Antenna height (m)	0
Antenna type	Dipole-D

Receiver details

Assigned frequency	408.837500 MHz
Bandwidth	12.5000 kHz
Freq. assign. ID	0000692632
Transmitter power	N/A
EIRP	N/A
Emission designator	10K1F3E

Antenna details

Antenna ID	70085
Antenna polarisation	V - Vertical linear
Antenna azimuth	
Antenna height (m)	0
Antenna type	Dipole-D

Special Conditions applying to Station 2

The level of power in the adjacent channel must not exceed -16dBm.

The level of all discreet spurious components, measured at the output of the transmitter, must not exceed -30dBm.

Technical characteristics

Below is a summary of the technical characteristics of the licensed service. Further technical details not displayed here may be found on the ACMA website.

Supplementary Station Site

Station 3:

Site details

Site ID	40001
Site address	Rail Shunting Yards, HORNSBY NSW 2077
Co-ordinates (GDA94)	Latitude: -33.69193691 Longitude: 151.10548743

Transmitter details

Assigned frequency	418.287500 MHz
Bandwidth	12.5000 kHz
Freq. assign. ID	0000692633
Transmitter power	25.00 W
EIRP	41.00 W
Emission designator	10K1F3E

Antenna details

Antenna ID	70085
Antenna polarisation	V - Vertical linear
Antenna azimuth	
Antenna height (m)	0
Antenna type	Dipole-D

Receiver details

Assigned frequency	408.837500 MHz
Bandwidth	12.5000 kHz
Freq. assign. ID	0000692634
Transmitter power	N/A
EIRP	N/A
Emission designator	10K1F3E

Antenna details

Antenna ID	70085
Antenna polarisation	V - Vertical linear
Antenna azimuth	
Antenna height (m)	0
Antenna type	Dipole-D

Special Conditions applying to Station 3

The level of power in the adjacent channel must not exceed -16dBm.

The level of all discreet spurious components, measured at the output of the transmitter, must not exceed -30dBm.