# Apparatus Licence

Issued by Delegate of the Australian Communications and Media Authority



Licensee details				
Customer ID	210019			
Licensee	Country Fire Authority			
Licensee address	PO Box 701, MOUNT WAVERLEY, VIC 3149			
Licence details				
Licence service	Land Mobile			
Licence subservice	Land Mobile System - > 30MHz			
Licence number	1304022/1			
Callsign	VL3NI			
Date of issue	04/02/2024			
Date of effect	04/02/2024			
Date of expiry	15/03/2025			
Licence conditions				

Your licence is subject to conditions set out in the *Radiocommunications Act 1992*. Your licence may also be subject to such other licence conditions as determined by the ACMA (in licence condition determinations) from time to time, and is also subject to special conditions as detailed on this licence.

The conditions that are imposed on a licence vary according to the type of licence issued, the service being operated and the section of the *Radiocommunications Act 1992* under which the licence has been issued. For further information about the conditions that apply to your licence, please contact the ACMA (see contact details below).

#### Rights of appeal

A decision by the ACMA to impose further conditions or revoke or vary the conditions of your licence may be reviewable. If you are affected by, and dissatisfied with, such a decision you may apply to the ACMA to have the ACMA reconsider the decision under section 288 of the *Radiocommunications Act 1992*.

An application for reconsideration must state the reasons for the request, and should be sent to the Customer Service Centre, Australian Communications and Media Authority, PO Box 78, Belconnen, ACT, 2616. Applications for review of decisions can be made using the R051 - Application for review of Decision form, available on the ACMA website.

#### Important

An application for the ACMA to reconsider a decision to impose or vary licence conditions must be made to the ACMA within 28 days of the day on which you are informed of the decision. An application for reconsideration made after that time may not be accepted.

### ACMA contact details

Customer Service Centre PO Box 78 BELCONNEN ACT 2616

Telephone: 1300 850 115 Email: info@acma.gov.au

ACMA website: www.acma.gov.au

Certain information contained in this licence record will be disclosed in the Register of Radiocommunications Licences (RRL), established and maintained pursuant to Part 3.5 of the *Radiocommunications Act 1992*.

## Advisory Notes applying to licence no.: 1304022/1

Conditions applicable to the operation of Land Mobile System station(s) authorised under this licence can be found in the Radiocommunications Licence Conditions (Apparatus Licence) Determination and the Radiocommunications Licence Conditions (Land Mobile Licence) Determination. Copies of these determinations are available from the ACMA and from the ACMA home page (www.acma.gov.au).

### **Technical characteristics**

Below is a summary of the technical characteristics of the licensed service. Further technical details not displayed here may be found on the ACMA website.

### **Main Station Site**

Station 1:

Site details				
Site ID	12008			
Site address	Silver Comm Site, Lot 13 Kinglake Rd, KINGLAKE VIC 3763			
Co-ordinates (GDA94)	Latitude: -37.515708	Longitude:	145.316285	
Transmitter details				
Assigned frequency	161.112500 MHz			
Bandwidth	12.5000 kHz			
Freq. assign. ID	0000704365			
Transmitter power	50.00 W			
EIRP	83.00 W			
Emission designator	10K1F3E			
Antenna details				
Antenna ID	71			
Antenna polarisation	V - Vertical linear			
Antenna azimuth				
Antenna height (m)	0			
Antenna type	Coaxial Dipole-D			
Receiver details				
Assigned frequency	161.112500 MHz			
Bandwidth	12.5000 kHz			
Freq. assign. ID	0000704369			
Transmitter power	N/A			
EIRP	N/A			
Emission designator	10K1F3E			
Antenna details				
Antenna ID	71			
Antenna polarisation	V - Vertical linear			
Antenna azimuth				
Antenna height (m)	0			
Antenna type	Coaxial Dipole-D			

# Special Conditions applying to Station 1

When the transmitter is coupled to an antenna the level of all discrete spurious components caused by the transmitter & measured at the connection to the antenna must not exceed -30 DBM. Broadband noise floor of the transmitter measured at the same point must not exceed -47 DBM in a 16 kHz bandwidth for frequency offsets greater than 300 kHz from the transmit frequency.

An efficient cavity filter must be fitted between the receiver and the antenna.