

Apparatus Licence

Issued by Delegate of the Australian Communications and Media Authority



Licensee details

Customer ID	77908
Licensee	Volunteer Marine Rescue Gladstone Inc
Licensee address	PO Box 797, GLADSTONE DC, QLD 4680

Licence details

Licence service	Maritime Coast
Licence subservice	Limited Coast Assigned System
Licence number	134085/1
Callsign	VM4RG
Date of issue	21/06/2023
Date of effect	21/06/2023
Date of expiry	31/07/2024

Licence conditions

Your licence is subject to conditions set out in the *Radiocommunications Act 1992*. Your licence may also be subject to such other licence conditions as determined by the ACMA (in licence condition determinations) from time to time, and is also subject to special conditions as detailed on this licence.

The conditions that are imposed on a licence vary according to the type of licence issued, the service being operated and the section of the *Radiocommunications Act 1992* under which the licence has been issued. For further information about the conditions that apply to your licence, please contact the ACMA (see contact details below).

Rights of appeal

A decision by the ACMA to impose further conditions or revoke or vary the conditions of your licence may be reviewable. If you are affected by, and dissatisfied with, such a decision you may apply to the ACMA to have the ACMA reconsider the decision under section 288 of the *Radiocommunications Act 1992*.

An application for reconsideration must state the reasons for the request, and should be sent to the Customer Service Centre, Australian Communications and Media Authority, PO Box 78, Belconnen, ACT, 2616. Applications for review of decisions can be made using the R051 - Application for review of Decision form, available on the ACMA website.

Important

An application for the ACMA to reconsider a decision to impose or vary licence conditions must be made to the ACMA within 28 days of the day on which you are informed of the decision. An application for reconsideration made after that time may not be accepted.

ACMA contact details

Customer Service Centre
PO Box 78
BELCONNEN ACT 2616

Telephone: 1300 850 115
Email: info@acma.gov.au

ACMA website: www.acma.gov.au

Advisory Notes applying to licence no.: 134085/1

Conditions applicable to the operation of Limited Coast Assigned System authorised under this licence can be found in the Radiocommunications Licence Conditions (Apparatus Licence) Determination and the Radiocommunications Licence Conditions (Maritime Coast Licence) Determination. Copies of these determinations are available from the ACMA and from the ACMA home page (www.acma.gov.au).

Prior to 4 September 2002 this licence authorised the operation of one Limited Coast Assigned Station.

Technical characteristics

Below is a summary of the technical characteristics of the licensed service. Further technical details not displayed here may be found on the ACMA website.

Main Station Site

Station 1:

Site details

Site ID	17098
Site address	Air Sea Rescue Site, LADY LARCOM QLD 4680
Co-ordinates (GDA94)	Latitude: -23.805067 Longitude: 151.126417

Transmitter details

Assigned frequency	161.725000 MHz
Bandwidth	25.0000 kHz
Freq. assign. ID	0000503283
Transmitter power	50.00 W
EIRP	83.00 W
Emission designator	16K0F3E

Antenna details

Antenna ID	1
Antenna polarisation	
Antenna azimuth	
Antenna height (m)	0
Antenna type	Unknown antenna type, size or specifications-

Receiver details

Assigned frequency	157.125000 MHz
Bandwidth	25.0000 kHz
Freq. assign. ID	0000503286
Transmitter power	N/A
EIRP	N/A
Emission designator	16K0F3E

Antenna details

Antenna ID	1
Antenna polarisation	
Antenna azimuth	
Antenna height (m)	0
Antenna type	Unknown antenna type, size or specifications-

Special Conditions applying to Station 1

An efficient cavity filter must be fitted between the transmitter and the antenna.

When the transmitter is coupled to an antenna the level of all discrete spurious components caused by the transmitter & measured at the connection to the antenna must not exceed -30 DBM. Broadband noise floor of the transmitter measured at the same point must not exceed -47 DBM in a 16 kHz bandwidth for frequency offsets greater than 300 kHz from the transmit frequency.

An efficient cavity filter must be fitted between the receiver and the antenna.

The level of power in the adjacent channel must not exceed -22dBm.

The level of all discrete spurious components, measured at the output of the transmitter, must not exceed -30dBm.