Apparatus Licence

Issued by Delegate of the Australian Communications and Media Authority

Australian Government | acma

Licensee details

Customer ID	336005
Licensee	Anthony Smith
Licensee address	34 Mulquinneys Road, BRAUNSTONE, NSW 2460

Licence details

Licence service	Amateur
Licence subservice	Amateur Repeater
Licence number	164674/3
Callsign	VK2RCV
Date of issue	04/08/2023
Date of effect	04/08/2023
Date of expiry	02/08/2024

Licence conditions

Your licence is subject to conditions set out in the *Radiocommunications Act 1992*. Your licence may also be subject to such other licence conditions as determined by the ACMA (in licence condition determinations) from time to time, and is also subject to special conditions as detailed on this licence.

The conditions that are imposed on a licence vary according to the type of licence issued, the service being operated and the section of the *Radiocommunications Act 1992* under which the licence has been issued. For further information about the conditions that apply to your licence, please contact the ACMA (see contact details below).

Rights of appeal

A decision by the ACMA to impose further conditions or revoke or vary the conditions of your licence may be reviewable. If you are affected by, and dissatisfied with, such a decision you may apply to the ACMA to have the ACMA reconsider the decision under section 288 of the *Radiocommunications Act 1992*.

An application for reconsideration must state the reasons for the request, and should be sent to the Customer Service Centre, Australian Communications and Media Authority, PO Box 78, Belconnen, ACT, 2616. Applications for review of decisions can be made using the R051 - Application for review of Decision form, available on the ACMA website.

Important

An application for the ACMA to reconsider a decision to impose or vary licence conditions must be made to the ACMA within 28 days of the day on which you are informed of the decision. An application for reconsideration made after that time may not be accepted.

ACMA contact details

Customer Service Centre
PO Box 78
BELCONNEN ACT 2616

Telephone: 1300 850 115
Email: info@acma.gov.au

ACMA website: www.acma.gov.au

Certain information contained in this licence record will be disclosed in the Register of Radiocommunications Licences (RRL), established and maintained pursuant to Part 3.5 of the *Radiocommunications Act 1992.*

Advisory Notes applying to licence no.: 164674/3

Conditions applicable to the operation of Amateur Repeater station(s) authorised under this licence can be found in the Radiocommunications Licence Conditions (Apparatus Licence) Determination and the Radiocommunications Licence Conditions (Amateur Licence) Determination. Copies of these determinations are available from the ACMA and from the ACMA home page (www.acma.gov.au).

Technical characteristics

Below is a summary of the technical characteristics of the licensed service. Further technical details not displayed here may be found on the ACMA website.

Main Station Site — Station 1:

Site details	
Site ID	8202
Site address	NSWTA 25m Lattice Tower, Pine Brush State Forest, PILLAR VALLEY NSW 2462
Co-ordinates (GDA94)	Latitude: -29.635007 Longitude: 153.157229

Transmitter details	
Assigned frequency	439.912500 MHz
Bandwidth	12.5000 kHz
Freq. assign. ID	0001977062
Transmitter power	50.00 W
EIRP	83.00 W
Emission designator	11K3F9W
Antenna details	
Antenna ID	40117
Antenna polarisation	V - Vertical linear
Antenna azimuth	
Antenna height (m)	10
Antenna type	Parallel array of vertical dipoles-D

Receiver details	
Assigned frequency	434.912500 MHz
Bandwidth	12.5000 kHz
Freq. assign. ID	0001977063
Transmitter power	N/A
EIRP	N/A
Emission designator	11K3F9W
Antenna details	
Antenna ID	40117
Antenna polarisation	V - Vertical linear
Antenna azimuth	
Antenna height (m)	10
Antenna type	Parallel array of vertical dipoles-D

Technical characteristics

Below is a summary of the technical characteristics of the licensed service. Further technical details not displayed here may be found on the ACMA website.

Main Station Site **Station 2:**

Site details	
Site ID	8202
Site address	NSWTA 25m Lattice Tower, Pine Brush State Forest, PILLAR VALLEY NSW 2462
Co-ordinates (GDA94)	Latitude: -29.635007 Longitude: 153.157229

Transmitter details	
Assigned frequency	146.675000 MHz
Bandwidth	25.0000 kHz
Freq. assign. ID	0001038176
Transmitter power	30.00 W
EIRP	
Emission designator	16K0F3E
Antenna details	
Antenna ID	64
Antenna polarisation	V - Vertical linear
Antenna azimuth	
Antenna height (m)	0
Antenna type	Ground Plane-C

Receiver details	
Assigned frequency	146.075000 MHz
Bandwidth	25.0000 kHz
Freq. assign. ID	0001038177
Transmitter power	N/A
EIRP	N/A
Emission designator	16K0F3E
Antenna details	
Antenna ID	64
Antenna polarisation	V - Vertical linear
Antenna azimuth	
Antenna height (m)	0
Antenna type	Ground Plane-C

Technical characteristics

Below is a summary of the technical characteristics of the licensed service. Further technical details not displayed here may be found on the ACMA website.

Main Station Site **Station 3:**

Site details	
Site ID	8202
Site address	NSWTA 25m Lattice Tower, Pine Brush State Forest, PILLAR VALLEY NSW 2462
Co-ordinates (GDA94)	Latitude: -29.635007 Longitude: 153.157229

Transmitter details	
Assigned frequency	144.900000 MHz
Bandwidth	25.0000 kHz
Freq. assign. ID	0001038178
Transmitter power	30.00 W
EIRP	
Emission designator	16K0F2D
Antenna details	
Antenna ID	71
Antenna polarisation	V - Vertical linear
Antenna azimuth	
Antenna height (m)	0
Antenna type	Coaxial Dipole-D

Receiver details	
Assigned frequency	144.900000 MHz
Bandwidth	25.0000 kHz
Freq. assign. ID	0001038179
Transmitter power	N/A
EIRP	N/A
Emission designator	16K0F2D
Antenna details	
Antenna ID	71
Antenna polarisation	V - Vertical linear
Antenna azimuth	
Antenna height (m)	0
Antenna type	Coaxial Dipole-D

Special Conditions applying to Station 3

When the transmitter is coupled to an antenna the level of all discrete spurious components caused by the transmitter & measured at the connection to the antenna must not exceed -30 DBM. Broadband noise floor of the transmitter measured at the same point must not exceed -47 DBM in a 16 kHz bandwidth for frequency offsets greater than 300 kHz from the transmit frequency.

The level of all discreet spurious components, measured at the output of the transmitter, must not exceed -30dBm.