## Apparatus Licence

Issued by Delegate of the Australian Communications and Media Authority



Licensee details	
Customer ID	1606147
Licensee	DBNGP (WA) Nominees Pty Ltd
Trading name	Dampier Bunbury Pipeline
Licensee address	Att: Dane Coetzee PO Box Z5267, SAINT GEORGES TERRACE, WA 6831

Licence details	
Licence service	Fixed
Licence subservice	Point to Multipoint
Licence number	1919829/1
Callsign	AXI416
Date of issue	04/09/2023
Date of effect	04/09/2023
Date of expiry	13/09/2024

### Licence conditions

Your licence is subject to conditions set out in the *Radiocommunications Act 1992*. Your licence may also be subject to such other licence conditions as determined by the ACMA (in licence condition determinations) from time to time, and is also subject to special conditions as detailed on this licence.

The conditions that are imposed on a licence vary according to the type of licence issued, the service being operated and the section of the *Radiocommunications Act 1992* under which the licence has been issued. For further information about the conditions that apply to your licence, please contact the ACMA (see contact details below).

#### Rights of appeal

A decision by the ACMA to impose further conditions or revoke or vary the conditions of your licence may be reviewable. If you are affected by, and dissatisfied with, such a decision you may apply to the ACMA to have the ACMA reconsider the decision under section 288 of the *Radiocommunications Act 1992*.

An application for reconsideration must state the reasons for the request, and should be sent to the Customer Service Centre, Australian Communications and Media Authority, PO Box 78, Belconnen, ACT, 2616. Applications for review of decisions can be made using the R051 - Application for review of Decision form, available on the ACMA website.

#### **Important**

An application for the ACMA to reconsider a decision to impose or vary licence conditions must be made to the ACMA within 28 days of the day on which you are informed of the decision. An application for reconsideration made after that time may not be accepted.

### **ACMA** contact details

Customer Service Centre PO Box 78 BELCONNEN ACT 2616

Telephone: 1300 850 115 Email: info@acma.gov.au

ACMA website: www.acma.gov.au

Certain information contained in this licence record will be disclosed in the Register of Radiocommunications Licences (RRL), established and maintained pursuant to Part 3.5 of the *Radiocommunications Act 1992*.

Fixed - Point to Multipoint Page 1 of 3

## Advisory Notes applying to licence no.: 1919829/1

Conditions applicable to the operation of Point to Multipoint station(s) authorised under this licence can be found in the Radiocommunications Licence Conditions (Apparatus Licence) Determination and the Radiocommunications Licence Conditions (Fixed Licence) Determination, the 'fixed licence lcd'. Copies of these determinations are available from the ACMA and from the ACMA home page (www.acma.gov.au).

Fixed - Point to Multipoint Page 2 of 3

### **Technical characteristics**

Below is a summary of the technical characteristics of the licensed service. Further technical details not displayed here may be found on the ACMA website.

### **Main Station Site**

Transmitter details

### Station 1:

Site details			
Site ID	47235		
Site address	Spur Site 8, DAMPIER WA 6714		
Co-ordinates (GDA94)	Latitude: -20.661447	Longitude:	116.729134

Assigned frequency	461.968750 MHz
Bandwidth	12.5000 kHz
Freq. assign. ID	0001054913
Transmitter power	5.00 W
EIRP	17.00 W
Emission designator	10K1F1D
Antenna details	
Antenna ID	80216
Antenna polarisation	V - Vertical linear
Antenna azimuth	
Antenna height (m)	46
Antenna type	Dipole-D
Receiver details	
Assigned frequency	452.468750 MHz
Bandwidth	12.5000 kHz
Freq. assign. ID	0001054916
Transmitter power	N/A
EIRP	N/A
Emission designator	10K1F1D
Antenna details	
Antenna ID	80216
Antenna polarisation	V - Vertical linear
Antenna azimuth	
Antenna height (m)	46
Antenna type	Dipole-D

# Special Conditions applying to Station 1

When the transmitter is coupled to an antenna the level of all discrete spurious components caused by the transmitter & measured at the connection to the antenna must not exceed -30 DBM. Broadband noise floor of the transmitter measured at the same point must not exceed -47 DBM in a 16 kHz bandwidth for frequency offsets greater than 300 kHz from the transmit frequency.

Fixed - Point to Multipoint Page 3 of 3