

Apparatus Licence

Issued by Delegate of the Australian Communications and Media Authority



Licensee details

Customer ID	1315002
Licensee	Motorola Solutions Australia Pty. Limited
Trading name	Motorola Australia AU504
Licensee address	Locked Bag 27, MOUNT WAVERLEY, VIC 3149

Licence details

Licence service	Fixed
Licence subservice	Point to Multipoint - Land Mobile Spec
Licence number	1951173/3
Callsign	VLA786
Date of issue	30/07/2021
Date of effect	30/07/2021
Date of expiry	16/08/2022

Licence conditions

Your licence is subject to conditions set out in the *Radiocommunications Act 1992*. Your licence may also be subject to such other licence conditions as determined by the ACMA (in licence condition determinations) from time to time, and is also subject to special conditions as detailed on this licence.

The conditions that are imposed on a licence vary according to the type of licence issued, the service being operated and the section of the *Radiocommunications Act 1992* under which the licence has been issued. For further information about the conditions that apply to your licence, please contact the ACMA (see contact details below).

Rights of appeal

A decision by the ACMA to impose further conditions or revoke or vary the conditions of your licence may be reviewable. If you are affected by, and dissatisfied with, such a decision you may apply to the ACMA to have the ACMA reconsider the decision under section 288 of the *Radiocommunications Act 1992*.

An application for reconsideration must state the reasons for the request, and should be sent to the Customer Service Centre, Australian Communications and Media Authority, PO Box 78, Belconnen, ACT, 2616. Applications for review of decisions can be made using the R051 - Application for review of Decision form, available on the ACMA website.

Important

An application for the ACMA to reconsider a decision to impose or vary licence conditions must be made to the ACMA within 28 days of the day on which you are informed of the decision. An application for reconsideration made after that time may not be accepted.

ACMA contact details

Customer Service Centre
PO Box 78
BELCONNEN ACT 2616

Telephone: 1300 850 115
Email: info@acma.gov.au

ACMA website: www.acma.gov.au

Advisory Notes applying to licence no.: 1951173/3

Conditions applicable to the operation of point to multipoint station(s) authorised under this licence can be found in the Radiocommunications Licence Conditions (Apparatus Licence) Determination and the Radiocommunications Licence Conditions (Fixed Licence) Determination, the 'fixed licence lcd'. Copies of these determinations are available from the ACMA and from the ACMA home page (www.acma.gov.au).

Technical characteristics

Below is a summary of the technical characteristics of the licensed service. Further technical details not displayed here may be found on the ACMA website.

Main Station Site

Station 1:

Site details	
Site ID	11596
Site address	120 Collins Street, MELBOURNE VIC 3000
Co-ordinates (GDA94)	Latitude: -37.813822 Longitude: 144.969482

Transmitter details	
Assigned frequency	503.625000 MHz
Bandwidth	12.5000 kHz
Freq. assign. ID	0000792228
Transmitter power	1.00 W
EIRP	10.00 W
Emission designator	10K1D7W

Antenna details	
Antenna ID	70030
Antenna polarisation	V - Vertical linear
Antenna azimuth	
Antenna height (m)	25
Antenna type	Colinear Vertical-U

Receiver details	
Assigned frequency	513.625000 MHz
Bandwidth	12.5000 kHz
Freq. assign. ID	0000792227
Transmitter power	N/A
EIRP	N/A
Emission designator	10K1D7W

Antenna details	
Antenna ID	70030
Antenna polarisation	V - Vertical linear
Antenna azimuth	
Antenna height (m)	25
Antenna type	Colinear Vertical-U

Advisory Notes applying to Station 1

Relocate into Harmonised Government Spectrum (HGS) Bands

Special Conditions applying to Station 1

When the transmitter is coupled to an antenna the level of all discrete spurious components caused by the transmitter & measured at the connection to the antenna must not exceed -30 DBM. Broadband noise floor of the transmitter measured at the same point must not exceed -47 DBM in a 16 kHz bandwidth for frequency offsets greater than 300 kHz from the transmit frequency.