## **Apparatus Licence**

Issued by Delegate of the Australian Communications and Media Authority



| Licensee details |                                       |
|------------------|---------------------------------------|
| Customer ID      | 1147558                               |
| Licensee         | Tasmanian Ports Corporation Pty. Ltd. |
| Trading name     | Tasports                              |
| Licensee address | GPO Box 202, HOBART, TAS 7001         |

| Licence details    |                               |
|--------------------|-------------------------------|
| Licence service    | Maritime Coast                |
| Licence subservice | Limited Coast Assigned System |
| Licence number     | 1959370/1                     |
| Callsign           | VZR695                        |
| Date of issue      | 24/07/2023                    |
| Date of effect     | 24/07/2023                    |
| Date of expiry     | 30/07/2024                    |

### Licence conditions

Your licence is subject to conditions set out in the *Radiocommunications Act 1992*. Your licence may also be subject to such other licence conditions as determined by the ACMA (in licence condition determinations) from time to time, and is also subject to special conditions as detailed on this licence.

The conditions that are imposed on a licence vary according to the type of licence issued, the service being operated and the section of the *Radiocommunications Act 1992* under which the licence has been issued. For further information about the conditions that apply to your licence, please contact the ACMA (see contact details below).

#### Rights of appeal

A decision by the ACMA to impose further conditions or revoke or vary the conditions of your licence may be reviewable. If you are affected by, and dissatisfied with, such a decision you may apply to the ACMA to have the ACMA reconsider the decision under section 288 of the *Radiocommunications Act 1992*.

An application for reconsideration must state the reasons for the request, and should be sent to the Customer Service Centre, Australian Communications and Media Authority, PO Box 78, Belconnen, ACT, 2616. Applications for review of decisions can be made using the R051 - Application for review of Decision form, available on the ACMA website.

#### **Important**

An application for the ACMA to reconsider a decision to impose or vary licence conditions must be made to the ACMA within 28 days of the day on which you are informed of the decision. An application for reconsideration made after that time may not be accepted.

### **ACMA** contact details

Customer Service Centre PO Box 78 BELCONNEN ACT 2616

Telephone: 1300 850 115 Email: info@acma.gov.au

ACMA website: www.acma.gov.au

Certain information contained in this licence record will be disclosed in the Register of Radiocommunications Licences (RRL), established and maintained pursuant to Part 3.5 of the *Radiocommunications Act 1992*.

## Advisory Notes applying to licence no.: 1959370/1

Conditions applicable to the operation of Limited Coast Assigned System authorised under this licence can be found in the Radiocommunications Licence Conditions (Apparatus Licence) Determination and the Radiocommunications Licence Conditions (Maritime Coast Licence) Determination. Copies of these determinations are available from the ACMA and from the ACMA home page (www.acma.gov.au).

### **Technical characteristics**

Below is a summary of the technical characteristics of the licensed service. Further technical details not displayed here may be found on the ACMA website.

### **Main Station Site**

**Transmitter details** 

### Station 1:

| Site details         |  |
|----------------------|--|
| Site ID              | 34252  |
| Site address         | Port Control Tower Burnie Wharf, BURNIE TAS 7320 |
| Co-ordinates (GDA94) | Latitude: -41.05637 Longitude: 145.908506        |

| Assigned frequency   | 156.600000 MHz      |
|----------------------|---------------------|
| Bandwidth            | 25.0000 kHz         |
| Freq. assign. ID     | 0000513832          |
| Transmitter power    | 50.00 W             |
| EIRP                 | 83.00 W             |
| Emission designator  | 16K0F3E             |
| Antenna details      |                     |
| Antenna ID           | 71                  |
| Antenna polarisation | V - Vertical linear |
| Antenna azimuth      |                     |
| Antenna height (m)   | 0                   |
| Antenna type         | Coaxial Dipole-D    |
| Receiver details     |                     |
| Assigned frequency   | 156.600000 MHz      |
| Bandwidth            | 25.0000 kHz         |
| Freq. assign. ID     | 0000513837          |
| Transmitter power    | N/A                 |
| EIRP                 | N/A                 |
| Emission designator  | 16K0F3E             |
| Antenna details      |                     |
| Antenna ID           | 71                  |
| Antenna polarisation | V - Vertical linear |
| Antenna azimuth      |                     |
| Antenna height (m)   | 0                   |
| Antenna type         | Coaxial Dipole-D    |

# **Special Conditions applying to Station 1**

When the transmitter is coupled to an antenna the level of all discrete spurious components caused by the transmitter & measured at the connection to the antenna must not exceed -30 DBM. Broadband noise floor of the transmitter measured at the same point must not exceed -47 DBM in a 16 kHz bandwidth for frequency offsets greater than 300 kHz from the transmit frequency.

The level of power in the adjacent channel must not exceed -22dBm.

### **Technical characteristics**

Below is a summary of the technical characteristics of the licensed service. Further technical details not displayed here may be found on the ACMA website.

### **Main Station Site**

Transmitter details

## Station 2:

| 34252                                   |   |  |
|---|---|--|
| Port Control Tower Burnie Wharf, BURNIE | TAS 7320                                |  |
| Latitude: -41.05637                     | _ongitude:                              | 145.908506                                       |
|   | Port Control Tower Burnie Wharf, BURNIE | Port Control Tower Burnie Wharf, BURNIE TAS 7320 |

| Transmitter details  |                     |
|----------------------|---------------------|
| Assigned frequency   | 156.300000 MHz      |
| Bandwidth            | 25.0000 kHz         |
| Freq. assign. ID     | 0000513838          |
| Transmitter power    | 50.00 W             |
| EIRP                 | 83.00 W             |
| Emission designator  | 16K0F3E             |
| Antenna details      |                     |
| Antenna ID           | 71                  |
| Antenna polarisation | V - Vertical linear |
| Antenna azimuth      |                     |
| Antenna height (m)   | 0                   |
| Antenna type         | Coaxial Dipole-D    |
| Receiver details     |                     |
| Assigned frequency   | 156.300000 MHz      |
| Bandwidth            | 25.0000 kHz         |
| Freq. assign. ID     | 0000513841          |
| Transmitter power    | N/A                 |
| EIRP                 | N/A                 |
| Emission designator  | 16K0F3E             |
| Antenna details      |                     |
| Antenna ID           | 71                  |
| Antenna polarisation | V - Vertical linear |
| Antenna azimuth      |                     |
| Antenna height (m)   | 0                   |
| Antenna type         | Coaxial Dipole-D    |
|                      |                     |

# **Special Conditions applying to Station 2**

The level of power in the adjacent channel must not exceed -22dBm.

When the transmitter is coupled to an antenna the level of all discrete spurious components caused by the transmitter & measured at the connection to the antenna must not exceed -30 DBM. Broadband noise floor of the transmitter measured at the same point must not exceed -47 DBM in a 16 kHz bandwidth for frequency offsets greater than 300 kHz from the transmit frequency.

### **Technical characteristics**

Below is a summary of the technical characteristics of the licensed service. Further technical details not displayed here may be found on the ACMA website.

### **Main Station Site**

### Station 3:

| Site details         |  |
|----------------------|--|
| Site ID              | 34252  |
| Site address         | Port Control Tower Burnie Wharf, BURNIE TAS 7320 |
| Co-ordinates (GDA94) | Latitude: -41.05637 Longitude: 145.908506        |
|                      |  |

| Transmitter details  |                     |  |
|----------------------|---------------------|--|
| Assigned frequency   | 156.400000 MHz      |  |
| Bandwidth            | 25.0000 kHz         |  |
| Freq. assign. ID     | 0000513842          |  |
| Transmitter power    | 50.00 W             |  |
| EIRP                 | 83.00 W             |  |
| Emission designator  | 16K0F3E             |  |
| Antenna details      |                     |  |
| Antenna ID           | 71                  |  |
| Antenna polarisation | V - Vertical linear |  |
| Antenna azimuth      |                     |  |
| Antenna height (m)   | 0                   |  |
| Antenna type         | Coaxial Dipole-D    |  |
| Receiver details     |                     |  |
| Assigned frequency   | 156.400000 MHz      |  |
| Bandwidth            | 25.0000 kHz         |  |
| Freq. assign. ID     | 0000513845          |  |
| Transmitter power    | N/A                 |  |
| EIRP                 | N/A                 |  |
| Emission designator  | 16K0F3E             |  |
| Antenna details      |                     |  |
| Antenna ID           | 71                  |  |
| Antenna polarisation | V - Vertical linear |  |
| Antenna azimuth      |                     |  |
| Antenna height (m)   | 0                   |  |
| Antenna type         | Coaxial Dipole-D    |  |

## **Special Conditions applying to Station 3**

The level of power in the adjacent channel must not exceed -22dBm.

When the transmitter is coupled to an antenna the level of all discrete spurious components caused by the transmitter & measured at the connection to the antenna must not exceed -30 DBM. Broadband noise floor of the transmitter measured at the same point must not exceed -47 DBM in a 16 kHz bandwidth for frequency offsets greater than 300 kHz from the transmit frequency.