Apparatus Licence

Issued by Delegate of the Australian Communications and Media Authority



Licensee details	
Customer ID	31823
Licensee	NSW Police Force
Trading name	Radio Engineering Services
Licensee address	Level 4 151-241 Goulburn St Sydney Police Centre,, SURRY HILLS, NSW 2010

Licence details	
Licence service	Land Mobile
Licence subservice	Land Mobile System - > 30MHz
Licence number	50920/1
Callsign	VKG
Date of issue	09/06/2023
Date of effect	09/06/2023
Date of expiry	01/07/2024

Licence conditions

Your licence is subject to conditions set out in the *Radiocommunications Act 1992*. Your licence may also be subject to such other licence conditions as determined by the ACMA (in licence condition determinations) from time to time, and is also subject to special conditions as detailed on this licence.

The conditions that are imposed on a licence vary according to the type of licence issued, the service being operated and the section of the *Radiocommunications Act 1992* under which the licence has been issued. For further information about the conditions that apply to your licence, please contact the ACMA (see contact details below).

Rights of appeal

A decision by the ACMA to impose further conditions or revoke or vary the conditions of your licence may be reviewable. If you are affected by, and dissatisfied with, such a decision you may apply to the ACMA to have the ACMA reconsider the decision under section 288 of the *Radiocommunications Act 1992*.

An application for reconsideration must state the reasons for the request, and should be sent to the Customer Service Centre, Australian Communications and Media Authority, PO Box 78, Belconnen, ACT, 2616. Applications for review of decisions can be made using the R051 - Application for review of Decision form, available on the ACMA website.

Important

An application for the ACMA to reconsider a decision to impose or vary licence conditions must be made to the ACMA within 28 days of the day on which you are informed of the decision. An application for reconsideration made after that time may not be accepted.

ACMA contact details

Customer Service Centre PO Box 78 BELCONNEN ACT 2616

Telephone: 1300 850 115 Email: info@acma.gov.au

ACMA website: www.acma.gov.au

Certain information contained in this licence record will be disclosed in the Register of Radiocommunications Licences (RRL), established and maintained pursuant to Part 3.5 of the *Radiocommunications Act 1992*.

Special Conditions applying to licence no.: 50920/1

When the transmitter is coupled to an antenna the level of all discrete spurious components caused by the transmitter & measured at the connection to the antenna must not exceed -30 DBM. Broadband noise floor of the transmitter measured at the same point must not exceed -47 DBM in a 16 kHz bandwidth for frequency offsets greater than 300 kHz from the transmit frequency.

Advisory Notes applying to licence no.: 50920/1

Conditions applicable to the operation of Land Mobile System station(s) authorised under this licence can be found in the Radiocommunications Licence Conditions (Apparatus Licence) Determination and the Radiocommunications Licence Conditions (Land Mobile Licence) Determination. Copies of these determinations are available from the ACMA and from the ACMA home page (www.acma.gov.au).

Technical characteristics

Below is a summary of the technical characteristics of the licensed service. Further technical details not displayed here may be found on the ACMA website.

Main Station Site

Station 1:

Site details	
Site ID	9962
Site address	Water Tank, Bauloora via, COOTAMUNDRA NSW 2590
Co-ordinates (GDA94)	Latitude: -34.556531 Longitude: 147.972318

Transmitter details		
Assigned frequency	469.112500 MHz	
Bandwidth	12.5000 kHz	
Freq. assign. ID	0000523644	
Transmitter power	50.00 W	
EIRP	83.00 W	
Emission designator	10K1F1E	
Antenna details		
Antenna ID	13182	
Antenna polarisation	V - Vertical linear	
Antenna azimuth		
Antenna height (m)	30	
Antenna type	Parallel array of vertical dipoles-D	
Receiver details		
Assigned frequency	459.112500 MHz	
Bandwidth	12.5000 kHz	
Freq. assign. ID	0000523647	
Transmitter power	N/A	
EIRP	N/A	
Emission designator	10K1F1E	
Antenna details		
Antenna ID	13182	
Antenna ID Antenna polarisation	13182 V - Vertical linear	
Antenna polarisation		

Special Conditions applying to Station 1

When the transmitter is coupled to an antenna the level of all discrete spurious components caused by the transmitter & measured at the connection to the antenna must not exceed -30 DBM. Broadband noise floor of the transmitter measured at the same point must not exceed -47 DBM in a 16 kHz bandwidth for frequency offsets greater than 300 kHz from the transmit frequency.

The level of power in the adjacent channel must not exceed -16dBm.

The level of all discreet spurious components, measured at the output of the transmitter, must not exceed -30dBm.

Technical characteristics

Below is a summary of the technical characteristics of the licensed service. Further technical details not displayed here may be found on the ACMA website.

Main Station Site

Station 2:

Site details	
Site ID	9962
Site address	Water Tank, Bauloora via, COOTAMUNDRA NSW 2590
Co-ordinates (GDA94)	Latitude: -34.556531 Longitude: 147.972318

Receiver details	
Assigned frequency	459.587500 MHz
Bandwidth	12.5000 kHz
Freq. assign. ID	0000523649
Transmitter power	N/A
EIRP	N/A
Emission designator	10K1F1E
Antenna details	
Antenna ID	13182
Antenna polarisation	V - Vertical linear
Antenna azimuth	
Antenna height (m)	30
Antenna type	Parallel array of vertical dipoles-D

Special Conditions applying to Station 2

When the transmitter is coupled to an antenna the level of all discrete spurious components caused by the transmitter & measured at the connection to the antenna must not exceed -30 DBM. Broadband noise floor of the transmitter measured at the same point must not exceed -47 DBM in a 16 kHz bandwidth for frequency offsets greater than 300 kHz from the transmit frequency.

The level of power in the adjacent channel must not exceed -16dBm.

The level of all discreet spurious components, measured at the output of the transmitter, must not exceed -30dBm.