Apparatus Licence

Issued by Delegate of the Australian Communications and Media Authority



Licensee details	
Customer ID	51920
Licensee	Banana Shire Council
Licensee address	PO Box 412, BILOELA, QLD 4715
Licence details	
Licence service	Fixed
Licence subservice	Point to Multipoint
Licence number	9800320/2
Date of issue	08/08/2023
Date of effect	08/08/2023
Date of expiry	26/07/2024
Licence condition	S

Your licence is subject to conditions set out in the *Radiocommunications Act 1992*. Your licence may also be subject to such other licence conditions as determined by the ACMA (in licence condition determinations) from time to time, and is also subject to special conditions as detailed on this licence.

The conditions that are imposed on a licence vary according to the type of licence issued, the service being operated and the section of the *Radiocommunications Act 1992* under which the licence has been issued. For further information about the conditions that apply to your licence, please contact the ACMA (see contact details below).

Rights of appeal

A decision by the ACMA to impose further conditions or revoke or vary the conditions of your licence may be reviewable. If you are affected by, and dissatisfied with, such a decision you may apply to the ACMA to have the ACMA reconsider the decision under section 288 of the *Radiocommunications Act 1992*.

An application for reconsideration must state the reasons for the request, and should be sent to the Customer Service Centre, Australian Communications and Media Authority, PO Box 78, Belconnen, ACT, 2616. Applications for review of decisions can be made using the R051 - Application for review of Decision form, available on the ACMA website.

Important

An application for the ACMA to reconsider a decision to impose or vary licence conditions must be made to the ACMA within 28 days of the day on which you are informed of the decision. An application for reconsideration made after that time may not be accepted.

ACMA contact details

Customer Service Centre PO Box 78 BELCONNEN ACT 2616

Telephone: 1300 850 115 Email: info@acma.gov.au

ACMA website: www.acma.gov.au

Certain information contained in this licence record will be disclosed in the Register of Radiocommunications Licences (RRL), established and maintained pursuant to Part 3.5 of the *Radiocommunications Act 1992*.

Advisory Notes applying to licence no.: 9800320/2

Conditions applicable to the operation of Point to Multipoint station(s) authorised under this licence can be found in the Radiocommunications Licence Conditions (Apparatus Licence) Determination and the Radiocommunications Licence Conditions (Fixed Licence) Determination, the 'fixed licence Icd'. Copies of these determinations are available from the ACMA and from the ACMA home page (www.acma.gov.au).

Technical characteristics

Below is a summary of the technical characteristics of the licensed service. Further technical details not displayed here may be found on the ACMA website.

Main Station Site

Station 1:

Site details					
Site ID	17740				
Site address	Council Site, BANANA RANGE QLD 4715				
Co-ordinates (GDA94)	Latitude: -24.448332	Longitude:	150.316012		
Transmitter details					
Assigned frequency	461.725000 MHz				
Bandwidth	25.0000 kHz				
Freq. assign. ID	0001049573				
Transmitter power	5.00 W				
EIRP	40.00 W				
Emission designator	16K0F2D				
Antenna details					
Antenna ID	70030				
Antenna polarisation	V - Vertical linear				
Antenna azimuth					
Antenna height (m)	0				
Antenna type	Colinear Vertical-U				
Receiver details					
Assigned frequency	452.225000 MHz				
Bandwidth	25.0000 kHz				
Freq. assign. ID	0001049574				
Transmitter power	N/A				
EIRP	N/A				
Emission designator	16K0F2D				
Antenna details					
Antenna ID	70030				
Antenna polarisation	V - Vertical linear				
Antenna azimuth					
Antenna height (m)	0				
Antenna type	Colinear Vertical-U				

Special Conditions applying to Station 1

The level of power in the adjacent channel must not exceed -16dBm.

The level of all discreet spurious components, measured at the output of the transmitter, must not exceed -30dBm.